51555W

Glass Powder

Description

51555W is a premixed lead free white LTCC powder designed for tape application which allows the production of high performance components and multilayer circuits.

Key Features

- Relatively low dielectric loss Plating bath resistance, hence, particularly suitable for high performance component manufacture In tape form this material is also compatible with Heraeus silver and gold conductor systems

Americas
Phone +1 610 825 6050
electronics.americas@heraeus.com

Asia Pacific
Phone +65 6571 7649
electronics.apac@heraeus.com

China
Phone +86 53 5815 9601
electronics.china@heraeus.com

Europe, Middle East and Africa
Phone +49 6181 35 4370
electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.

All changes are based on information displayed using the template data_sheet/HET/TFM/print_data_sheet.html.twig.
Version (last updated) 21 Aug 2026

Heraeus Electronics GmbH & Co.KG, 63450 Hanau, Germany
Web: www.heraeus-electronics.com

51555W

Glass Powder

Warranty

Material guaranteed to meet specifications for 12 months from date of manufacturing with proper storage.

Storage

Store in a dry, cool (5 - 25°C), dark place with container tightly shut. Allow paste to come to room temperature prior to opening. Spatulate well before using.

Americas	Asia Pacific	China	Europe, Middle East and Africa
Phone +1 610 825 6050	Phone +65 6571 7649	Phone +86 53 5815 9601	Phone +49 6181 35 4370
electronics.americas@heraeus.com	electronics.apac@heraeus.com	electronics.china@heraeus.com	electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.

All changes are based on information displayed using the template data_sheet/HET/TFM/print_data_sheet.html.twig.
Version (last updated) 21 Aug 2026

Heraeus Electronics GmbH & Co.KG, 63450 Hanau, Germany
Web: www.heraeus-electronics.com