

ET1801

End Termination

Description

ET1801 is a solderable Ag/Pd/Pt end termination designed for use on MLCC (multilayer ceramic chip capacitors). ET1801 offers excellent solderability and leach resistance.

Key Features

- Suitable rheology for machine dip application Excellent solderability and leach resistance Compatible on titanate ceramic bodies



This picture does not show the packaging of ET1801 and is solely intended for illustration purposes. The products are available in different packaging configurations and may change over time. Please refer to the latest safety data sheets for safety-relevant pictograms.

Typical Properties

Viscosity	30 – 40 Kcps Brookfield RVTSC4 – 14 spindle, 6R utility cup at 10 rpm, 25 °C
Metal	AgPdPt

Recommended Processing Guide

Process Temperature (TDS)	780 – 810 °C peak temperature Dwell time of 5 – 6 minutes at peak
---------------------------	---

Americas

Phone +1 610 825 6050

electronics.americas@heraeus.com

Asia Pacific

Phone +65 6571 7649

electronics.apac@heraeus.com

China

Phone +86 53 5815 9601

electronics.china@heraeus.com

Europe, Middle East and Africa

Phone +49 6181 35 4370

electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.

All changes are based on information displayed using the template data_sheet/HET/TFM/print_data_sheet.html.twig.
Version (last updated) 26 Feb 2026

Heraeus Electronics GmbH & Co.KG, 63450 Hanau, Germany
Web: www.heraeus-electronics.com