

IP9049H

Dielectric / Glaze

Description

IP9049H is a white dielectric, particularly developed for use as an acid-resistant overglaze on chip and standard resistors.

Key Features

- It can withstand plating solutions, eg. Ni baths with pH-values of 4-5 and Pb/Sn baths with pH-values of < 1
- Also resistant to mildly alkaline solutions



This picture does not show the packaging of IP9049H and is solely intended for illustration purposes. The products are available in different packaging configurations and may change over time. Please refer to the latest safety data sheets for safety-relevant pictograms.

Typical Properties

Viscosity	25-45 Pas (25 °C, D = 100/s)
Coverage	c. 111 cm ² /g (FFT: 15 µm)
Color	White

Recommended Processing Guide

Process Temperature (TDS)	Fire at 580-620 °C (peak) for 2 minutes, and with a total firing cycle time of c. 25-30 minutes.
Film Thickness	16-20 µm

Americas

Phone +1 610 825 6050

electronics.americas@heraeus.com

Asia Pacific

Phone +65 6571 7649

electronics.apac@heraeus.com

China

Phone +86 53 5815 9601

electronics.china@heraeus.com

Europe, Middle East and Africa

Phone +49 6181 35 4370

electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.

All changes are based on information displayed using the template data_sheet/HET/TFM/print_data_sheet.html.twig.
Version (last updated) 26 Feb 2026

Heraeus Electronics GmbH & Co.KG, 63450 Hanau, Germany
Web: www.heraeus-electronics.com