

PCD11465

Dielectric / Glaze

Description

PCD11465 is a red plating solution resistant resistor overglaze. PCD11465 improves the stability of laser or air-abrasive trimmed resistors by providing protection from plating baths, harsh environments, organic potting compounds and abrasive over-spray.

Key Features

- Minimizes resistance shift on re-fire Resistant to Ni and Sn plating solutions

Typical Properties

Viscosity	130 – 170 kcps Brookfield HBT SC4-14 spindle and 6R utility cup @ 10 rpm, 25°C
Solids	
Blendable	
Coverage	85-90 cm2 /gm (Calculated from 50 micron wet film)
Color	Red
Resistivity	
Laser Trim	
Rel. Dielectric Constant	
Dissipation Factor	
Insulation Resistance	
Breakdown Voltage	
Via resolution	

PCD11465

Dielectric / Glaze

Typical Properties (continued)	
Thermal Coefficient of Expansion (CTE)	
Solderability	
Recommended Processing Guide	
Printing Parameters	200-325 stainless steel mesh screen 0.5 mil emulsion Allow parts to level at room temperature for 1-3 minutes before drying.
Printing Speed	
Leveling	
Drying Temperature	150°C for 5-10 minutes
Process Temperature (TDS)	600°C to 630°C peak temperature Dwell time of 3 - 7 minutes at peak
Film Thickness	10-15 microns
Recommended Thinner	Heraeus RV-372
Paste Compatibility	

Americas
Phone +1 610 825 6050
electronics.americas@heraeus.com

Asia Pacific
Phone +65 6571 7649
electronics.apac@heraeus.com

China
Phone +86 53 5815 9601
electronics.china@heraeus.com

Europe, Middle East and Africa
Phone +49 6181 35 4370
electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.

PCD11465

Dielectric / Glaze

Warranty

Material guaranteed to meet specifications for 6 months from date of manufacturing with proper storage.

Storage

Store in a dry location at 5 – 25°C. DO NOT REFRIGERATE. Allow paste to come to room temperature prior to opening. Spatulate well before using, as settling may occur during storage.

Americas

Phone +1 610 825 6050

electronics.americas@heraeus.com

Asia Pacific

Phone +65 6571 7649

electronics.apac@heraeus.com

China

Phone +86 53 5815 9601

electronics.china@heraeus.com

Europe, Middle East and Africa

Phone +49 6181 35 4370

electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application. The Heraeus logo and Heraeus, figurative mark are trademarks or registered trademarks of Heraeus Holding GmbH or its affiliates. All rights reserved.